

Films

Toner
Water
(eco) Solvent
UVgel /UV
Latex

IJM763 Self Adhesive Gold Metallic Film Satin 100 um

Product Description

This PVC Free self-adhesive gold metallic polyester film is non reflective and features a warm colour rendering. Its gold appearance adds a luxurious look and feel to any application.

Physical Properties

Thickness facefilm	100 µm	ISO 534	Opacity	98%	ISO 2471
Weight	127 g/m ²	ISO 536	Adhesion	13,5 N/25mm	FINAT TM1
Total Thickness	160 µm	ISO 534	Perm Acryl glue	23 g/m ²	ISO 536
Total Weight	210 g/m ²	ISO 536	Max temp	90°	Celsius

All values listed are target values

Applications/features

Posters
High value labels
Signage
Window Graphics
Anti-glare satin surface
Opaque (98%) against rear lights
Excellent flatness

Available Widths (mm)

3"core	1270										
--------	------	--	--	--	--	--	--	--	--	--	--

Refer for our current offering to www.canon-europe.com/mediaguide

Storage Conditions

Shelf life: 1 year in a cool and dry environment. Temperature 10-25°C, Relative Humidity 50%
Repack opened rolls when not in use.

Print Conditions

Best results are obtained between 15-30°C and 30-60% RH.

Environment, Health & Safety

No Material Safety Data Sheet required.

Lamination Compatibility

Cold	Warm	Hot	Cold: pressure sensitive Warm: heat activated: 85°C - 95°C Hot: heat activated: 105°C -130°C
yes	no	no	

Outdoor Use

This film is suited for short term outdoor applications.

Colour Profiles

Canon develops high-quality colour profiles for media / ink / printer / RIP combinations.
Check availability of profiles for your printer on www.canon-europe.com/mediaguide

**Processing
Guidelines****Printing guidelines**

Allow material to adapt to room conditions for 24 hours before printing. It is recommended to handle the media with cotton gloves. Make sure that the media comes not into contact with grease, oil, silicon, and dirt to avoid printing defects. Insert the film with care in the printer. Incorrect loading can cause skewing or creasing. It is recommended to calibrate the printer before printing and to make a test print. Print results will vary for different printer ink combinations. Canon media profiles include recommended settings for ink restrictions and printer parameters. Depending on environment and application, printer parameters may have to be adjusted slightly in order to obtain the best results. For high-speed production printing, using an external drying unit is recommended.

Application guidelines

This film can be used outdoor without lamination. However, we recommend protecting its surface if it is subject to abrasion or any other mechanical influences. The film has very good lamination characteristics. Make sure that prints are completely dry and that all solvents are evaporated. It is recommended to let the prints dry at least 24 hours.

Standard disclaimer:

All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition 0615
© Canon Europa N.V., 2025

The Canon logo, consisting of the word "Canon" in a bold, red, sans-serif typeface.