CrystalPoint ™
Toner
(eco) Solvent
UVgel
WBI

Self-adhesive Specialities

LFM361 Self-adhesive Paper 90 g/m²

Product Description

Light embossed white self-adhesive paper with a removable rubber-based adhesive and a bleached kraft paper release liner. The paper is matte wood free

Physical Properties

Thickness paper	122 µm	ISO 534	Peel adhesion 90°	2.5 N/25mm	FINAT n°2 Stainless steel
Weight (excl. liner)	90 g/m²	ISO 536	Initial Tack	5 N/25mm	FINAT 9 Glass
Thickness liner	76 µm	ISO 534	Min. application temperature	-20 °C	
Weight liner	75 g/m²	ISO 536	Service temperature	-40/+70 °C	
Thickness total	212 µm	ISO 534			

All values listed are target values

Applications/ features

Self-adhesive posters and signs
Excellent image quality
Good wet strength
Excellent adhesion, repositionable.
Light embossed matte structure
German BfR approval for use in direct contact with dry or moist non fatty food

Available Widths (mm)

3”core	1000										

Refer for our current offering to www.canon-europe.com/mediaguide

Storage Conditions

Shelf life: 2 years, Temperature 25°C, Relative Humidity 40-50%
Repack opened rolls when not in use.

Print Conditions

Best results are obtained between 10-30°C and 40-70% RH.

Environment, Health & Safety

No Material Safety Data Sheet required. Waste not suitable for recycling.

Lamination Compatibility

Cold	Warm	Hot
yes	no	no

Cold: pressure sensitive
Warm: heat activated: 85°C - 95°C
Hot: heat activated: 105°C -130°C

Outdoor Use

This uncoated paper is not suited for outdoor use.

Colour Profiles

Canon develops high-quality colour profiles for media / ink / printer / RIP combinations.
Check availability of profiles for your printer on www.canon-europe.com/mediaguide

Processing Guidelines

Printing guidelines

LFM361 is compatible with ColorWave printers with CrystalPoint® technology. High quality print-modes are recommended for best results.

It is recommended to handle the media with cotton gloves Make sure that the media comes not into contact with grease, oil, silicon, and dirt to avoid printing defects. Insert media with care in the printers. Incorrect loading can cause skewing or creasing. Allow material to adapt to room conditions for 24 hours before printing. It is recommended to calibrate the printer before printing and to make a test print. Print results will vary for different printers.

Ink/toner restrictions and printer settings have to be set for specific printers to obtain the best results. Canon media profiles include recommended ink restrictions and printer settings for Canon supported printers.

For UVgel only compatible in matte mode

Application guidelines

The adhesive performance is excellent on a wide variety of substrates, combining good initial tack and adhesion with good removability to a variety of substrates. Application to porous substrates or prolonged exposure to UV light may adversely affect clean removability.
The best results- when applying the self-adhesive paper to a surface – are obtained if you wipe out the paper with a 100% felt squeegee.

Standard disclaimer:
All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition 0316
© Canon Europa N.V., 2026