

Toner
Water
(eco) Solvent
UVgel / UV
Latex

Product Description	A PVC Free matte coated smooth wallpaper. This lightweight non-woven wallpaper is the perfect choice for smooth, colorful and high resolution wall decorations
----------------------------	--

Physical Properties	Weight	180 g/m²	ISO 536	FR classification	C-s1,d0	EN 13501-1:2018
	Thickness	285 um	ISO 534	Opacity	>91%	ISO 2471
				VOC	A+	ISO 16000-9

**Applications/
features**

- Indoor wall covering
- Wall graphic
- Door coverage
- Interior Decoration
- Hospitality Venues

Available Widths (mm)

[illegible]

Environment, Health & Safety No Material Safety Data Sheet required.

Outdoor Use This non-woven wall covering is designed for indoor use only

Processing Guidelines

Printing guidelines

Allow material to adapt to room conditions for 24 hours before printing. It is recommended to handle the media with cotton gloves. Make sure that the media does not come into contact with grease, oil, silicon, and dirt to avoid printing defects.

Load the media with care in the printers. Incorrect loading can cause skewing or creasing. Use a take-up device to prevent wrinkling.

It is recommended to calibrate the printer before printing and to make a test print. Print results will vary for different printer/ink combinations.

Canon Colour profiles include recommended settings for ink restrictions and printer parameters. Depending on fluctuations in environment, printer, ink, media and applications, printer parameters may have to be adjusted slightly, in order to obtain the best results.

Application guidelines

Always pre-test the surface. The product has been used in many places under numerous possible conditions and has proven its reliability and performance.

The base surface should be carefully prepared:

- Remove all old wallpaper (To remove the remains of old adhesives try using a squirting bottle with water and a few squirts of washing up liquid. This works perfectly on most wallpaper adhesives)
- Remove all remnants
- Smooth out any rough surfaces
- Clean with a damp cloth
- Prior to beginning all surfaces should be dry.

Washability

In general; Digitally printed wallcovering can be washed. Slight or moderate soiling can be removed using a combination of mild detergent and a damp cloth. Dabbing – certainly not rubbing is recommended to lift the soil. It is important to rinse off with clean water (absorbent) cloth washing in a low to high vertical action to prevent moisture at skirting level. Bleach, abrasive cleaners and similar compounds must not be used.

Standard disclaimer:

All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon Inc.
canon.com

Canon Europe
canon-europe.com

English edition 0116
© Canon Europa N.V., 2024

