

Wall Covering

Toner
Water
(eco) Solvent
UVgel / UV
Latex

IJM710 Wall Covering Pearl Textile-back FR 360g/m²

Product Description A premium fabric back vinyl coated wall covering with a fine textured pearl surface. This wall covering product has a smooth Pearl appearance, giving it a stunning effect. Making it the right choice for high-end retail, hotel and residential applications

Physical Properties

Weight	360 g/m ²	ISO 536	FR classification	B-s1,d0	EN 13501-1
Thickness	440 µm	ISO 534			

All values listed are target values

Applications/features

Indoor wall covering
Wall graphics
Door coverage
Interior decoration
High end luxurious Wall Decoration

Durable and washable
Easy application, Paste-the-wall
No need to laminate
Bio Pruf treated. Preventing growth of bacteria and mold
CE-marking acc EN 15102:2007 +A1:2011

Available Widths (mm)

3"core	1300										
--------	------	--	--	--	--	--	--	--	--	--	--

Refer for our current offering to www.canon-europe.com/mediaguide

Storage Conditions

Shelf life: 1 year. Temperature 10-35°C, Relative Humidity 30-75%
Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours before printing.

Print Conditions

Best results are obtained between 18-25°C and 35-70% RH.
Optimal print conditions may differ from printer-type

Environment, Health & Safety

No Material Safety Data Sheet required. Handle waste and used material as industrial waste.

Lamination Compatibility

Cold	Warm	Hot
no	no	no

Cold: pressure sensitive
Warm: heat activated: 85°C - 95°C
Hot: heat activated: 105°C -130°C

Outdoor Use

This textile backed wall covering product is designed for indoor use only

Colour Profiles

Canon develops high-quality colour profiles for media / ink / printer / RIP combinations.
Check availability of profiles for your printer on www.canon-europe.com/mediaguide

Processing Guidelines

Printing guidelines

Allow material to adapt to room conditions for 24 hours before printing. It is recommended to handle the media with cotton gloves. Make sure that the media comes not into contact with grease, oil, silicon, and dirt to avoid printing defects. Load the media with care in the printers. Incorrect loading can cause skewing or creasing. Use a take-up device to prevent wrinkling. It is recommended to calibrate the printer before printing and to make a test print. Print results will vary for different printer/ink combinations. Canon Colour profiles include recommended settings for ink restrictions and printer parameters. Depending on fluctuations in environment, printer, ink, media and applications, printer parameters may have to be adjusted slightly, in order to obtain the best results.

Application guidelines

Always pre-test the surface. The product has been used in many places under numerous possible conditions and has proven its reliability and performance.

The base surface should be carefully prepared:

- Remove all old wallpaper (To remove the remains of old adhesives try using a squirting bottle with water and a few squirts of washing up liquid. This works perfectly on most wallpaper adhesives)
- Remove all remnants
- Smooth out any rough surfaces
- Clean with a damp cloth
- Prior to beginning all surfaces should be dry.

Adhesives

Heavy duty wallcovering adhesive BK 10 (manual) or BK 23 (industrial), or similar PVA substitute.

Washability

In general; Digitally printed wallcovering can be washed. Slight or moderate soiling can be removed using a combination of mild detergent and a damp cloth. Dabbing – certainly not rubbing is recommended to lift the soil. It is important to rinse off with clean water (absorbent) cloth washing in a low to high vertical action to prevent moisture at skirting level. Bleach, abrasive cleaners and similar compounds must not be used.

Standard disclaimer:

All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.