

Toner
Latex
(eco) Solvent
UVgel
Screen

Coated papers

IJM817 Self Adhesive Paper MC Silk FSC 130 g/m²

Product Description Self-adhesive paper for high quality multicolor, digital printed posters and other advertising material at an economical price level. This paper has a soft silk coating for excellent readability. Very well suited for Litho Lamination

Physical Properties

Weight (paper)	130 g/m ²	ISO 536	Adhesive strength	17 N/25mm	FTM 9
Weight total	200 g/m ²	ISO 536	Opacity	97%	ISO 2471
Thickness (paper+glue)	135 µm	ISO 2470/1	Gloss Hunter	62%	ISO 8254-1
Thickness total	185 µm	ISO 534	Brightness	90%	ISO 2470/1

All values listed are target values

Applications/features

Posters
Advertising Material
Labels for food
Home Applications
Litho Lamination
Wide temperature range – 40 to 60°C
Can be applied at 0°C, due to unique character of glue (rubber hotmelt glue)
PVC Free

Available Widths (mm)

3" Core	1067	1370	1600								
---------	------	------	------	--	--	--	--	--	--	--	--

Refer for our current offering to www.canon-europe.com/mediaguide

Storage Conditions

Temperature 10°-30°C, Relative Humidity 30-70%.
Rewind tightly and repack opened rolls when not in use. Allow material to adapt to room conditions 24 hours before printing.

Print Conditions

Best results at 21°C and 30-65% RH.

Environment, Health & Safety

No Material Safety Data Sheet required. Waste suitable for recycling.

Lamination Compatibility

Cold	Warm	Hot	Cold: pressure sensitive Warm: heat activated: 85°C - 95°C Hot: heat activated: 105°C -130°C
yes	no	No	

Outdoor Use

This material is for indoor use.

Colour Profiles

Canon develops high-quality colour profiles for media / ink / printer / RIP combinations.
Check availability of profiles for your printer on www.canon-europe.com/mediaguide



**Processing
Guidelines**

Printing guidelines

Allow material to adapt to room conditions for 24 hours before printing.
It is recommended to handle the media with cotton gloves. Load the media with care in the printer. Incorrect loading can cause skewing. It is recommended to calibrate the printer before printing and to make a test print. Print results will vary for different printer ink combinations. Ink restrictions and printer settings have to be set for specific printer-ink combinations to obtain the best results. Canon media profiles will set recommended ink restrictions and printer-settings for Canon supported printers.

Application guidelines

Designed for use in ambient and chill environment, particularly good performance in chill environment if the application surface is moist or very high initial adhesion is required. Good low temperature performance once labelled. Very good adhesion to non-polar surfaces.

The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

Standard disclaimer:

All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.