

Films

Toner
(eco) Solvent
UVgel / UV
Latex
CrystalPoint

IJM764 Rigid PVC Film Satin FR 410 µm

Product Description

A special coated rigid PVC film with high stability. The coating is featured by minor reflections, brilliant colors and good scratch resistance

Physical Properties

Weight film	660 g/m ²	ISO 536	Opacity	> 99 %	ISO 2471
Thickness film	410 µm	ISO 534	Flame Retardant	B, s1, do	EN13501-1

*All values listed are target values

Applications/features

Indoor signs and promotions
Displays, Pop-up displays
Outdoor signage
Suitable for UVgel and UV curable inks
Tear resistant hard PVC base
High image definition and color brilliance
Good scratch resistance

Available Widths (mm)

3"core	914	1067	1372							
--------	-----	------	------	--	--	--	--	--	--	--

Refer for our current offering to www.canon-europe.com/mediaguide

Storage Conditions

Shelf life: 18 months. Temperature 10-30°C, Relative Humidity 35-65%
Repack opened rolls when not in use.

Print Conditions

Best results are obtained between 15-25°C and 30-65% RH.

Environment, Health & Safety

No Material Safety Data Sheet required.

Lamination Compatibility

Cold	Warm	Hot	Cold: pressure sensitive Warm: heat activated: 85°C - 95°C Hot: heat activated: 105°C -130°C
yes	no	no	

Outdoor Use

Suited for short to media term outdoor use.

Colour Profiles

Canon develops high-quality colour profiles for media / ink / printer / RIP combinations.
Check availability of profiles for your printer on www.canon-europe.com/mediaguide

**Processing
Guidelines****Printing guidelines**

Allow material to adapt to room conditions for 24 hours before printing. It is recommended to handle the media with cotton gloves. Make sure that the media comes not into contact with grease, oil, silicon, and dirt to avoid printing defects. Load the media with care in the printers. Incorrect loading can cause skewing or creasing. Use a take-up device to prevent wrinkling. It is recommended to calibrate the printer before printing and to make a test print. Print results will vary for different printer/ink combinations. Canon media profiles include recommended settings for ink restrictions and printer parameters.

Application guidelines

The film can be easily mounted with and removed from double-sided adhesive tape without any problems.

We advise only to only use sharp cutter blades while cutting laminated popup panels. Cutting with a blunt blade can cause a burr at the edges and the panels can get scratches. To avoid mechanical influences lamination is highly advised. Before lamination the print has to be completely dry otherwise there is the risk of lumps. The lamination may have influences on the flatness of the film.

Standard disclaimer:

All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon Inc.
canon.com

Canon Europe
canon-europe.com

English edition 0116
© Canon Europa N.V., 2026

The Canon logo, consisting of the word "Canon" in a bold, red, sans-serif typeface.